

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 099 602 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
16.05.2001 Bulletin 2001/20

(51) Int Cl.7: **B60R 7/04**, B60N 3/10,
B60N 2/28

(21) Application number: **00309307.7**

(22) Date of filing: **23.10.2000**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Partch, Thomas William**
Trenton, Michigan 48183 (US)
• **Bahr, Wayne Edward**
Livonia, Michigan 48152 (US)

(30) Priority: **10.11.1999 US 437774**

(74) Representative: **Messulam, Alec Moses et al**
A. Messulam & Co. Ltd.,
43-45 High Road
Bushey Heath, Bushey, Herts WD23 1EE (GB)

(71) Applicant: **Ford Global Technologies, Inc.**
Dearborn, Michigan 48126 (US)

(54) Storage assembly

(57) A storage assembly 10 which is adapted for use within a vehicle of the type having conventional child safety seat anchors or brackets 12, 14, and a conventional vehicle seat 16 including a seat bottom or cushion

portion 18 and a backrest portion 20. Assembly 10 includes a storage module 22, and two fastening members 24, 26 which are adapted to be respectively and removably coupled to brackets 12, 14.




Fig. 1

EP 1 099 602 A1

Description

[0001] This invention relates to a storage assembly and more particularly, to a storage assembly which may be removably attached to a pair of child safety seat brackets.

[0002] Many automotive vehicles are or soon will be required to provide and include anchors or bracket type members for securing aftermarket child safety seats to conventional and/or "factory provided" vehicle seats. These brackets are of a standard size, shape, and configuration; are mounted and/or are to be mounted/ placed in standard predetermined locations upon the vehicle seats, and have a standard spacing arrangement; and are described for example and without limitation in Federal Motor Vehicle Safety Standard 225. More particularly, these brackets are or will be required to be rigidly mounted to the vehicle seat and/or to the vehicle body and to be accessible at and/or to protrude from the "junction" of the seat backrest and the seat bottom.

[0003] While these brackets offer vehicle owners, operators, and providers of child safety seats a standardised arrangement and mechanism for rigidly placing and/or operatively attaching a child seat within a vehicle, they presently provide substantially no other utility.

[0004] Additional secure storage space is typically desired within the passenger compartment of a vehicle, although it cannot frequently and/or usually be provided due to the spatial constraints imposed by the various devices and assemblies which are utilised within and which co-operatively form the vehicle. For this reason, attempts have been made to provide storage assemblies which can be removably secured within the passenger compartment of a vehicle.

[0005] Such prior attempts include, for example and without limitation, storage containers or assemblies which are adapted to be secured to the vehicle's seats by use of a conventional seat belt, or by use of a member which is frictionally and removably secured and/or placed within and between the engaged or abutting seat back and the seat cushion. These prior containers suffer from some drawbacks. This is, since these containers do not fixedly and rigidly attach to the vehicle seat and/or body, but rather rely on a relatively "loose" or unstable seat belt or frictional attachments, they often became dislodged, tip, or overturn while the vehicle is being driven. More particularly, during relatively high vehicle accelerations/decelerations or during cornering, these prior assemblies/devices often undesirably "travel within" the passenger compartment.

[0006] Thus, it is desirable to provide a storage assembly which overcomes at least some of the drawbacks of prior storage assemblies and which may be used in combination with child safety seat brackets, thereby maximising the utility of the brackets while concomitantly providing additional and substantially secure storage space within a vehicle passenger compartment.

[0007] According to a first aspect of the present invention a storage assembly for use in combination with a vehicle of the type including a seat having a bottom portion which is joined with a backrest portion and a pair of child safety seat brackets which are disposed between said joined bottom portion and said backrest portion, said storage assembly comprising: a storage module which is adapted to be placed upon said bottom portion of said seat; and a pair of fastening members which are attached to said storage module and which are selectively and removably attachable to said brackets, thereby allowing said storage module to be selectively secured to said brackets.

[0008] According to a second aspect of the present invention a method is provided for mounting a storage assembly within a vehicle of the type having a seat including a cushion, and first and second brackets disposed in relative close proximity to the cushion. The method includes the steps of providing a storage container having a first latch and a second latch; removably securing the first latch to the first bracket; and removably securing the second latch to the second bracket, thereby securing the storage container to the first and second brackets.

[0009] The present invention will now be described further, by way of example, with reference to the accompanying drawings, in which:

Figure 1 is a perspective view of a storage assembly which is made in accordance with the teachings of the preferred embodiment of the invention, and which is operatively attached to conventional child safety seat brackets;

Figure 2 is a perspective view of the storage assembly which is shown in Figure 1 and which is removed from the child safety seat brackets;

Figure 3 is a partial view of the latch assembly which is employed within the storage assembly of Figure 1 and which is in an "unlatched" state;

Figure 4 is a partial view of the latch assembly which is employed within the storage assembly of Figure 1 and which is in a partially latched state;

Figure 5 is a partial view of the latch assembly which is employed within the storage assembly of Figure 1 and which is in a "latched" state;

Figure 6 is a partial view of a vehicle seat having conventional child safety seat brackets;

Figure 7 is a perspective view of a storage assembly which is made in accordance with the teachings of a second embodiment of the invention;

Figure 8 is a perspective view of a storage assembly which is made in accordance with the teachings of a third embodiment of the invention;

Figure 9 is a perspective view of a storage assembly which is made in accordance with the teachings of a fourth embodiment of the invention;

Figure 10 is a perspective view of a storage assembly which is made in accordance with the teachings

of a fifth embodiment of the invention; and Figure 11 is a perspective view of a storage assembly which is made in accordance with the teachings of a sixth embodiment of the invention.

[0010] Referring now to Figures 1-5, there is shown a storage assembly 10 which is made in accordance with the teachings of the preferred embodiment of the invention and which is adapted for use within a vehicle of the type having conventional child safety seat anchors, members, or brackets 12, 14, and a conventional vehicle seat 16 including a seat bottom or cushion portion 18 and a backrest portion 20. As shown, assembly 10 includes a storage container, receptacle, or module 22, and two fastening members or assemblies 24, 26 which are adapted to be respectively, selectively, and removably coupled to brackets 12, 14. Fastening assemblies 24, 26 are respectively, pivotally and conventionally attached to module 22 by conventional joint members 28, 30, such as pins, bolts, or screws.

[0011] The conventional child safety seat brackets 12, 14 illustrated in Figures 1 - 5 are fixedly coupled to and/or with the vehicle seat 18 which is rigidly attached to the body of the vehicle. Particularly, brackets 12, 14 are coupled to the crossbar 31 of seat 18 and are accessible at the juncture 34 of the seat bottom 18 and the seat backrest 20, as best shown in Figure 6. The centres of symmetry 44, 46 of brackets 12, 14 are separated by a predetermined distance 48.

[0012] In the preferred embodiment of the invention, module 22 is manufactured from a relatively rigid and durable material such as metal, plastic, or a composite material. Module 22 includes a generally flat bottom portion 23 which abuttingly rests and/or resides upon the top surface 32 of seat cushion 18. In one non-limiting embodiment bottom portion 23 is shaped to conform to the top surface 32 of seat cushion 18. Module 22 preferably includes a plurality of storage compartments having various shapes and sizes, effective to accommodate, store, and/or contain a variety of objects and items. For example and without limitation, the non-limiting embodiment of module 22 illustrated in Figures 1 and 2 includes generally circular compartments 60, 62, and 64 in which items such as and without limitation beverage containers, change, or cans may be stored, and generally rectangular compartments 66 and 68 in which other items and/or objects may be stored.

[0013] Other alternate and non-limiting embodiments of module 22 are illustrated in Figures 7 - 11. Particularly, in Figure 7 there is shown a module 70 made in accordance with the teachings of a second embodiment of the invention and including a flexible net or elastic member 72 which is attached to a generally rectangular housing 74 and which is adapted to securely store, hold, and/or maintain items within housing 74. Figure 8 illustrates a module 80 made in accordance with the teachings of a third embodiment of the invention, which includes a generally rectangular raised portion or surface 82 on which

a child may place items, such as a book, food, or toys, and a recessed portion or surface 84 which includes generally circular compartments 86, 87, and 88 in which items such as and without limitation beverage containers, change, or cans may be stored. Figure 9 illustrates a module 90 made in accordance with the teachings of a fourth embodiment of the invention. Module 90 includes a generally rectangular storage compartment 92 and a lid member 94 which is conventionally and pivotally mounted to compartment 92. In one non-limiting embodiment, compartment 92 includes separate conventional compartments and/or devices which are designed, shaped, and/or sized to store "business" or office type items, such as cellular phone 96 and a laptop or portable computer 98. Figure 100 illustrates a module 100 made in accordance with the teachings of a fifth embodiment of the invention and including a conventional cage 102 for transporting an animal or pet. Figure 11 illustrates a module 110 made in accordance with the teachings of a sixth embodiment of the invention and including a raised tray portion 112 which is fixedly attached to four substantially identical elongated legs or support members 114, 116, 118, and 120, which co-operatively support portion 112 at a predetermined and desired height above surface 32 of seat cushion 18. Members 114 - 120 are attached to rail members 122 and 124, which rest upon surface 32 of seat cushion 18. As shown in Figure 11, module 110 provides a raised surface 126 which a child may utilise (e.g., for eating, writing, or playing).

[0014] In the preferred embodiment of the invention, fastening assemblies 24, 26 comprise conventional latching mechanisms, and are attached in relative close proximity to the bottom 23 of module 22. Assemblies 24, 26 each respectively include substantially identical slots 36, 38 which are each respectively adapted to receive brackets 12, 14, and substantially identical and retractable latches 40, 42 which are respectively adapted to selectively secure brackets 12, 14 within slots 36, 38. In the preferred embodiment of the invention, assemblies 24, 26 are separated by a distance 50 which is substantially identical to distance 48, thereby allowing assemblies 24, 26 to be substantially aligned and engaged with the centres of symmetry 44, 46 of brackets 12, 14. In the preferred embodiment of the invention, assemblies 24, 26 further include conventional latch release buttons, levers, or members 52, 54. In other alternate embodiments, members 24, 26 may comprise any type of conventional fasteners such as and without limitation, straps, clamps, hooks, elastic attachments, or any other type of member adapted to be securely and removably coupled to brackets 12, 14.

[0015] In order to efficiently utilise the available child seat brackets 12, 14, according to the teachings of the preferred embodiment of the invention, assembly 10 is adapted to be selectively and removably placed onto seat cushion 18 and attached to brackets 12, 14. Particularly, in operation, fastening assemblies 24, 26 are

respectively aligned with brackets 12, 14. As best shown in Figures 3 - 5, assemblies 10, 24 and 26 are co-operatively and collectively moved in the direction of arrow 56, thereby allowing slots 36, 38 to respectively receive brackets 12, 14. As assemblies 24, 26 are forced in the direction of arrow 56, brackets 12, 14 engage latches 40, 42, thereby causing latches 40, 42 to retract as best shown in Figure 4. Once brackets 12, 14 reach the end of slots 36, 38, latches 40, 42 return to their original position thereby securing brackets 12, 14 within assemblies 24, 26.

[0016] Once assemblies 24, 26 have been connected to brackets 12, 14, module 22 is rested on seat bottom 18. Joints 28, 30 allow assemblies 24, 26 to pivot in the direction of arrows 58, thereby allowing module 22 to rest in a substantially horizontal position upon seat bottom 18. Assembly 10 can be removed from brackets 12, 14 by depressing latch release levers 52, 54. In this manner, it should be appreciated that assembly 10 provides additional utility for conventional child safety seat brackets and additional secure storage space within a vehicle. Furthermore, assembly 10 provides additional storage space within the passenger compartment of a vehicle which is fixedly secured to members (e.g. brackets 12, 14) which are rigidly attached to the vehicle seat and/or the vehicle body. Moreover, assembly 10 allows a user to choose from several secure locations within the vehicle (e.g. each seat having child safety brackets) at which assembly 10 may be fixedly and rigidly secured.

Claims

1. A storage assembly for use in combination with a vehicle of the type including a seat (16) having a bottom portion (18) which is joined with a backrest portion (20) and a pair of child safety seat brackets (12,14) which are disposed between said joined bottom portion (18) and said backrest portion (20), said storage assembly comprising:

a storage module (22) which is adapted to be placed upon said bottom portion (18) of said seat (16); and
a pair of fastening members (24,26) which are attached to said storage module (22) and which are selectively and removably attachable to said brackets (12,14), thereby allowing said storage module (22) to be selectively secured to said brackets (12,14).

2. A storage assembly as claimed in Claim 1, wherein said storage module comprises a plurality of compartments.
3. A storage assembly as claimed in Claim 1 or Claim 2, wherein said storage module is made from plas-

tic.

4. A storage assembly as claimed in any one of Claims 1 to 3, wherein each of said fastening members comprises a latch.
5. A storage assembly as claimed in any one of the preceding claims, wherein each of said fastening members comprises a release lever for removing said fastening members from said brackets.
6. A storage assembly as claimed in any one of the preceding claims, wherein each of said fastening members comprises a strap.
7. A storage assembly as claimed in any one of the preceding claims, wherein said fastening members are attached to said storage module by way of a pair of joints which allow said fastening members to pivot with respect to said storage module.
8. A storage assembly as claimed in any one of the preceding claims, wherein said storage module comprises a generally rectangular housing in which certain items may be stored and a flexible net which is attached to said housing and which is effective to secure said certain items within said housing.
9. An assembly for use within a vehicle of the type having a seat including a seat cushion and a pair of members which are rigidly attached to said seat, said assembly comprising:

a module having a bottom portion which selectively resides upon said seat cushion; and
a pair of fasteners which are coupled to said first portion and which are selectively and removably attachable to said members, thereby allowing said module to be removably secured to said members.

10. A method for mounting a storage assembly within a vehicle of the type having a seat including a cushion, and first and second brackets disposed in relative proximity to said cushion, said method comprising the steps of:

providing a storage container having a bottom portion and a first and second fastener coupled to said storage container in relative close proximity to said bottom portion;
removably coupling said first fastening member to said first bracket; and
removably coupling said second fastening member to said second bracket, thereby removably securing said storage container to said first and said second bracket.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 30 9307

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 0 878 347 A (RENAULT) 18 November 1998 (1998-11-18)	9	B60R7/04 B60N3/10 B60N2/28
Y	* the whole document *	1,4-7,10	
Y	DE 197 26 385 C (KNORR, RÜDIGER) 6 August 1998 (1998-08-06)	1,4-7,10	
A	* column 3, line 53 - column 4, line 20; figures 1-4 *	8,9	
A	DE 41 37 576 A (AUDI AG) 19 May 1993 (1993-05-19)	1,4-7	
A	* column 4, line 12 - column 5, line 53; figures 1-10 *		
A	WO 90 08671 A (KAVANAGH, JOHANNA, ANNA, MARIA ET AL.) 9 August 1990 (1990-08-09)	1-3,8	
A	* abstract; figures 1-7 *		
A	DE 298 14 444 U (C.ROB. HAMMERSTEIN GMBH & CO. KG) 19 November 1998 (1998-11-19)	1,4-7	
A	* claim 1; figure 2 *		TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	EP 0 936 104 A (RENAULT) 18 August 1999 (1999-08-18)	1,4-7	B60R B60N
A	* the whole document *		
A	EP 0 622 266 A (REGIE NATIONALE DES USINES RENAULT) 2 November 1994 (1994-11-02)	1,9,10	
	* column 2, line 45 - line 55; figures 1,2 * -----		
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 8 February 2001	Examiner Cuny, J-M
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P04/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 30 9307

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

08-02-2001

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
EP 0878347	A	18-11-1998	FR	2763292 A	20-11-1998
DE 19726385	C	06-08-1998	EP	0885769 A	23-12-1998
DE 4137576	A	19-05-1993	NONE		
WO 9008671	A	09-08-1990	NONE		
DE 29814444	U	19-11-1998	EP	0979752 A	16-02-2000
EP 936104	A	18-08-1999	FR	2774956 A	20-08-1999
EP 622266	A	02-11-1994	FR	2704492 A	04-11-1994
			DE	69401724 D	27-03-1997
			DE	69401724 T	03-07-1997
			ES	2097616 T	01-04-1997
			JP	6305346 A	01-11-1994
			US	5443239 A	22-08-1995

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82